



# 4100 POWER 15W-50

**Gasoline and Diesel Engines**

**Technosynthèse**

## TYPE OF USE

Specially designed for high performance engines, all gasoline or Diesel engines, Turbo or naturally aspirated, multivalves, with carburettor or with injection, with or without catalytic converter.  
Suitable for all types of fuel : standard, unleaded, Diesel fuel, LPG.  
All driving conditions : City, Road, Highway.

## PERFORMANCE

STANDARDS	ACEA A3 / B3
APPROVALS	API <b>SL</b> / CF
	VW 505 00 / VW 501 01 quality
	Mercedes Benz page 229.1

*\* The new standard API **SL** is more stringent than API **SJ** in terms of ageing resistance (average drain interval increased), requires anti-oxidation properties that maintain a constant viscosity avoiding sludge and deposits in the crankcase, anti-wear properties and dispersent power*

The synthetic base stock provides high lubricating power and protects perfectly the engine while in intensive use on road, highway or in town.

The high performing anti-wear additivation results in reduction of engine internal frictions and increases life duration by wear reduction.

High viscosity at high temperature (SAE 50) is fully adapted to engines prone to oil consumption.

Very efficient anti-deposit and anti-black sludge power which keeps the engine clean.

Anti-oxidation, Anti-corrosion, Anti-foam properties.

## RECOMMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.  
MOTUL 4100 Power 15W-50 can be mixed with synthetic or mineral oils.

## PROPERTIES

Viscosity grade	SAE J 300	<b>15W-50</b>
Density at 15°C (59°F)	ASTM D1298	0.882
Viscosity at 100°C (212°F)	ASTM D445	19.7 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)	ASTM D445	154 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	147
Pour point	ASTM D97	-30°C / -22°F
Flash point	ASTM D92	230°C / 446°F
TBN	ASTM D 2896	8.0 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - TEL : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site : [www.motul.fr](http://www.motul.fr)

3862

05/04